

Combijet JE30-1310D

Hot & Cold Water Pressure Cleaner

Pump Specifications

Working Pressure	30-110 bar / 435-1595 PSI
Max. Pressure	150 bar / 2175 GPM
Flow rate	330-660 l/h / 1.52-2.91 GPM
Max. inlet temperature	40° C
Max. outlet temperature	90° C

Motor Specifications

Electric Motor	3 kW / 4 HP
RPM	2800 @ 50 Hz
Power Supply	1 phase 230V 50Hz

Machine Specifications

Diesel tank	14 l / 3.7 gal
Detergent tank	2.5 l / 0.66 gal
Fuel consumption	2.83 l/h / 0.75 gal/h
Heat output	38 kW
Machine Dimensions (LXWXH)	80 X 55 X 83 cm
Weight	55 kg / 121 lbs



Key Features

T.S. *Total Stop*

Total Stop

When trigger gun is released, the pump stops automatically, avoiding any element damage during the by-pass phase. Pulling the trigger starts the pump automatically. This ensures max. pump protection.

Standard Features and Equipment

- Three ceramic coated pistons, brass axial pump head with built-in bypass valve
- Electric Cable - 5 meter
- Ultra high pressure hose - 8 meter
- *Pressure regulator
- Gun: Trigger operated
- Lance with jet nozzle
- Total Stop
- Suction and delivery S/S valves
- Vertical burner with high thermal efficiency steel coil
- Temperature regulation gauge
- Diesel pump with by-pass valve
- Detergent built-in tank for indirect suction
- Glycerin pressure gauge
- Ergonomic handle
- Power cable holder
- Accessory holder
- Operator and spares manual

